



P1	P2	P1	P2
1	1	14	14
2	2	15	15
3	3	16	16
4	4	17	17
5	5	18	18
6	6	19	19
7	7	20	20
8	8	21	21
9	9	22	22
10	10	23	23
11	11	24	24
12	12	25	25
13	13	SHELL	SHELL

Anschlusskabel D-SUB
 25 pol.D-SUB Stecker>25 pol.D-SUB Buchse

SUB-D cable
 25 pin SUB-D plug>25 pin SUB-D jack

- Belegung: seriell 1:1
- Innenleiter: CCS
- Isolierung: PVC
- Gewicht: 162 g
- Kontaktwiderstand: 10 Ohm max.
- Isolationswiderstand: 5 MOhm min.
- RoHS-konform

- Wiring: serial 1:1
- Inner conductor: CCS
- cable jacket PVC
- Weight: 162 g
- Contact resistance: 10 Ohm max.
- Insulation resistance: 5 MOhm min.
- RoHS compliant

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	tf	CAK D-SUB 180 25M/25F	
18.05.2018	tf	gepr.:	tf		
		Norm:	Zeichnungs-Nr.:		von
Änderungen vorbehalten / Subject to change				50541	

