



| Product | Name | Speaker Cable | | | | | | |
|-----------|---------------|-----------------------------------|-------|-----------------------------------|--|----------------------------|----------------------------|--|
| Conductor | Material | Copper Coated Aluminum | | Electrical Characteristics (20°C) | Max.Conductor DC Resistanc at 20°C (Ω/M) 0.019 | | | |
| | Nom.O.D. (mm) | 2x30/0.25 (2x1.5mm ²) | Up | | +0.02 | Rated Voltage (V) | ≤36V | |
| | | | Down | | -0.02 | | | |
| | External O.D. | 3mm×2c | Up | | +0.05 | Sheath Physical Properties | Rated Temperature(°C) 70°C | |
| Down | | | -0.05 | | | | | |
| Jacket | Surface | Smooth | | View | | | | |
| | Material | PVC(complies RoHS Reach) CPR(Eca) | | Drawn By | | | | |
| | | | | Page | | | | |

| no. | Packaging | Length (m) | color |
|-------|------------|------------|-------------|
| 67720 | Cable coil | 10 | transparent |
| 67721 | Cable coil | 25 | transparent |
| 67722 | Cable coil | 50 | transparent |
| 15019 | Cable Reel | 100 | transparent |
| 67747 | Cable coil | 10 | white |
| 67748 | Cable coil | 25 | white |
| 67749 | Cable coil | 50 | white |
| 27523 | Cable Reel | 100 | white |
| 67732 | Cable coil | 10 | red/black |
| 67733 | Cable coil | 25 | red/black |
| 67734 | Cable coil | 50 | red/black |
| 15023 | Cable Reel | 100 | red/black |

Eca Fire class (CPR) according to DIN EN 13501-6

| Änderungen | | | Datum | Name | Bezeichnung | Blatt |
|--|------|--------|------------|------|--|-------|
| Datum | Name | gez.: | 12.08.2021 | TL | LSK 2x1,5mm ² | 1/1 |
| 12.08.2021 | TL | gepr.: | | | | |
| | | Norm: | | | | |
| Änderungen vorbehalten / Subject to change | | | | | Zeichnungs-Nr.:27523 15019 15023 67749 67722 67734 67748 67721 67733 67747 67720 67732 | von |

